



Retail In Operation

High Performance Compact Size

RMP-130

Mobile Printer
(Wifi & Bluetooth)



Features

- Fast Print Speed : 5 ips
- Ultra-fast through-put
- 256MB SDRAM & 8G Flash memory
- All-in-one Bluetooth WLAN
- NFC for easy Bluetooth pairing
- Die-cast aluminum frame for ultimate ruggedness
- Durable and resistant to water and dust
- S-linerless solution supported
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Belt Strap, Car Charger

Possibilities & Beyond



Ontario, Canada
www.retailinoperation.com



Specifications



PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
Up to 5ips (127mm/sec)

Print Width
RMP-130 : Up to 3.1" (72mm)

Resolution
203 dpi (8dots/mm)

Memory
8GB or 16GB
DDR3 256MB

Battery Voltage / Capacity
7.2V / 2500mAh.
7.2V / 5000mAh. (Optional)

Sensor
Paper end, Gap,
Black mark, Cover open



INTERFACES

Standard
USB-C / USB 2.0
Bluetooth Smart Ready (BT4.2+BLE)
Wi-Fi (802.11 a/b/g/n/ac) Combo
• TKIP and AES encryption
• WPA and WPA2
• 802.1x (with WPA or WPA2)
• EAP-TTLS, EAP-TLS, PEAP (MSCHAPv2)
• Supports Certificates and Private Key (PEM) Upload
• Support for Soft AP, Infrastructure Mode
• NFC for easy Bluetooth pairing



SOFTWARE

Emulations
ESC / POS, CPCL, ZPL Command compatible

Drivers
Windows Driver(XP ~, Server2003 ~),
Window CE & Mobile Driver & SDK
(CE 4.2~, Mobile 5.0~), Linux Driver,
Mac Driver, OPOS Driver,
JavaPOS Driver, iOS SDK,
Android(6.0 ~) SDK
S-MDM
SSM & SCM



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
RMP-130 : 4.6" x 6.2" x 3.1"
(117.6 x 157.5 x 80mm)

Weight
RMP-130 : 1.56lbs / 709g
(With battery)

Display
TFT LCD (Color) 27.7 X 27.7mm



MEDIA CHARACTERISTICS

Media Type
RMP-130:Thermal Receipt,
Label / Linerless Label(Max. Restick)

Media Width
RMP-130 : 1.96" ~ 3.14" (50~80mm)

Media Core Diameter
0.4" (12.5mm ± 0.5mm)

Media Roll Diameter
RMP-130 : 2.62" (66.5mm)

Thickness
0.06 ~ 0.16mm



ACCESSORIES

Standard
USB C-type cable, Adaptor(RMP-130)
Belt strap,
Battery, Thermal roll paper,
Cleaning Pen

Optional
Set Cradle(RMP-130), Shoulder Strap,
5000mAh Extended Capacity Battery,
Single-bay Battery Cradle,
Battery Charging Cradle



OPERATING CHARACTERISTICS

Operating Temperature
-4 ~ 131° (-20 ~ 55°)

Operating Humidity
10 ~ 90%

Storage Temperature
-22 ~ 149° (-30 ~ 65°)

Storage Humidity
10 ~ 90%

Dust-and Water-resistance Rating
IP54 certified

Drop Rating
RMP-130 : 6.7 ft / 2.1m to concrete



BARCODES

1D
EAN-8, EAN-8(+2+5), EAN-13,
EAN-13(+2+5), Codabar, Code11,
Code39, Code93, Code128, ITF,
LUPC-A(+2+5), UPC-E, UPC-E(+2+5),
Planet, UPC-A etc

2D
QR, PDF417, MicroPDF417, Maxicode,
Datamatrix, Aztec, RSS14, TLC39



FONTS / GRAPHICS

Character Type
Font A(12x24), Font B(9x17),
Asian Font(KOR,JPN,CHN-GB2312,
CHNBig5), Font0/1/2/4/5/6/7,
Resident TTF, Downloadable TTF,
FontA~H, FontGS, Resident TTF(Font0),
Font 1~8

Characters per line (CPL)
RMP-130 : Font A (12 x 24) : 48cpl
Font B (9 x 17) : 64cpl
• Only for ESC / POS

Character set
95 Alphanumeric, 14 International,
128 x 18 Graphic
• Only for ESC / POS